

Description

WS 1805 S is an innovative ceramic protective coating for welding processes. With a single application it forms a dry film, effectively protecting welding equipment for up to 8 hours. No cleaning of the equipment is necessary, thus reducing costs and improving productivity. Compatible with painting processes.

Features

- Ceramic coating, oil-free.
- Increases productivity by 11%.
- The applied film dries in seconds.
- Consumable costs are reduced by up to 70%.
- Excellent adhesion of the protective film.
- Protects nozzles, contact tips and positioners.
- A single application ensures protection for an entire shift.

Applications

- MIG/MAG hand torches.
- Plasma and laser cutting torches.
- MIG/MAG robotic torches.
- Tools, parts and work areas.

Instructions for use

- Shake the spray vigorously.
- Dismantle the nozzle and spray on the parts to be protected, assemble the nozzle and spray on the inside and outside.
- Purge upside down after use.



Technical Data

Property	Specification/Method	Value
Reference	- - - - -	WS 1805 S
Aspect	- - - - -	Liquid
Colour	- - - - -	White
Density	- - - - -	2200 kg/m3
Maximum temperature	Dry Film	1200°C



Whale Spray S.L.

P.I. Ametlla Park.
L'Ametlla del Vallés.
08480 - Barcelona, Spain.
T. : +34 93 882 77 12
whalespray@whalespray.com

All data contained in this document are based on experience and laboratory tests. The wide range of equipment and environmental conditions as well as unforeseen human factors may influence the application results to a greater or lesser extent. For this reason we advise you to check the compatibility of the product before use. This information is based on reliable experience, but is merely indicative.